| ASTM Number              | Description   |
|--------------------------|---|
| A 36/A 36M—08            | Description Specification for Carbon Structural Steel   |
| A 153/A 153M—05          | Specification for Caroon Structural Steel  Specification for Zinc Coating (Hot-dip) on Iron and Steel Hardware  |
| 7 133/K 133WI—U3         | Standard Specification for Chromium and Chromium-nickel Stainless Steel Plate, Sheet and  |
| A 240/A 240M—09a         | Strip for Pressure Vessels and for General Applications   |
| A 252-98 (2007)          | Specification for Welded and Seamless Steel Pipe Piles  |
| A 283/A 283M—03(2007)    | Specification for Low and Intermediate Tensile Strength Carbon Steel Plates   |
| A 307—07b                | Specification for Carbon Steel Bolts and Studs, 60,000 psi Tensile Strength   |
|                          |   |
| A 416/A 416M—06          | Specification for Steel Strand, Uncoated Seven-wire for Prestressed Concrete  |
| A 463/A 463M—06          | Standard Specification for Steel Sheet, Aluminum-coated, by the Hot-dip Process   |
| A 572/A 572M—07          | Specification for High-strength Low-alloy Columbium-vanadium Structural Steel   |
| A 588/A 588M—05          | Specification for High-strength Low-alloy Structural Steel with 50 ksi (345 MPa) Minimum Yield Point with Atmospheric Corrosion Resistance  |
| A 615/A 615M—09          | Specification for Deformed and Plain Billet-steel Bars for Concrete Reinforcement   |
|                          | Specification for Steel Sheet, Zinc-coated Galvanized or Zinc-iron Alloy-coated Galvannealed  |
| A 653/A 653M—08          | by the Hot-dip Process  |
| A 690/A 690M—07          | Standard Specification for High-strength Low-alloy Nickel, Copper, Phosphorus Steel H-piles and Sheet Piling with Atmospheric Corrosion Resistance for Use in Marine Environments |
| A 706/ A 706M—09         | Specification for Low-alloy Steel Deformed and Plain Bars for Concrete Reinforcement  |
| A 722/A 722M—07          | Specification for Uncoated High-strength Steel Bar for Prestressing Concrete  |
|                          | Specification for Steel Sheet, Metallic-coated by the Hot-dip Process and Prepainted by the   |
| A 755/A 755M—03(2008)    | Coil-coating Process for Exterior Exposed Building Products   |
| A 792/A 792M—08          | Specification for Steel Sheet, 55% Aluminum-zinc Alloy-coated by the Hot-dip Process  |
|                          | Standard Specification for Steel Sheet Zinc-5 percent, Aluminum Alloy-coated by the Hot-dip   |
| A 875/A 875M—06          | Process   |
| A 913/A 913M—07          | Specification for High-strength Low-alloy Steel Shapes of Structural Quality, Produced by   |
|                          | Quenching and Self-tempering Process (QST)  |
| A 924/A 924M—08a         | Standard Specification for General Requirements for Steel Sheet, Metallic-coated by the Hot-dip Process   |
| A 992/A 992M—06a         | Standard Specification for Structural Shapes  |
| B 42—02e01               | Specification for Seamless Copper Pipe, Standard Sizes  |
| B 43—98(2004)            | Specification for Seamless Red Brass Pipe, Standard Sizes   |
| В 68—02                  | Specification for Seamless Copper Tube, Bright Annealed (Metric)  |
| B 88—03                  | Specification for Seamless Copper Water Tube  |
| B 101—07                 | Specification for Lead-coated Copper Sheet and Strip for Building Construction  |
| В 209—07                 | Specification for Aluminum and Aluminum Alloy Steel and Plate   |
| B 251—02e01              | Specification for General Requirements for Wrought Seamless Copper and Copper-alloy Tube  |
| В 280—03                 | Specification for Seamless Copper Tube for Air Conditioning and Refrigeration Field Service   |
| В 370—09                 | Specification for Cold-rolled Copper Sheet and Strip for Building Construction  |
| B 695—04                 | Standard Specification for Coatings of Zinc Mechanically Deposited on Iron and Steel Strip for Building Construction  |
| C 5—03                   | Specification for Quicklime for Structural Purposes   |
| C 22/C 22M—00 (2005) e01 | Specification for Gypsum  |
| C 27—98 (2008)           | Specification for Standard Classification of Fireclay and High-alumina Refractory Brick   |
| C 28/C 28M—00 (2005)     | Specification for Gypsum Plasters   |
| C 31/C 31M—08b           | Practice for Making and Curing Concrete Test Specimens in the Field   |
| C 33/C33M—08             | Specification for Concrete Aggregates   |
| C 34—03                  | Specification for Structural Clay Load-bearing Wall Tile  |
| C 35—01(2005)            | Specification for Inorganic Aggregates for Use in Gypsum Plaster  |
| C 55—06e01               | Specification for Concrete Building Brick   |
| C 56—05                  | Specification for Structural Clay Nonload Bearing Tile  |
| C 59/C 59M—00 (2006)     | Specification for Gypsum Casting and Molding Plaster  |
| C 61/C 61M—00 (2006)     | Specification for Gypsum Keene's Cement   |
| C 62—08                  | Specification for Building Brick (Solid Masonry Units Made from Clay or Shale)  |
| C 67—08                  | Test Methods of Sampling and Testing Brick and Structural Clay Tile   |
| C 73—05                  | Specification for Calcium Silicate Face Brick (Sand-lime Brick)   |
| C /3—03                  | Specification for Calcium Sincate Face Drick (Sand-Iline Drick)   |

| ASTM Number                 | Description   |
|-----------------------------|---|
| C 90—08                     | Specification for Loadbearing Concrete Masonry Units  |
| C 91—05                     | Specification for Masonry Cement  |
| C 94/C 94M—09               | Specification for Ready-mixed Concrete  |
| C 126—99 (2005)             | Specification for Ceramic Glazed Structural Clay Facing Tile, Facing Brick and Solid Masonry Units  |
| C 140—8a                    | Test Method Sampling and Testing Concrete Masonry Units and Related Units   |
| C 150—07                    | Specification for Portland Cement   |
| C 172—08                    | Practice for Sampling Freshly Mixed Concrete  |
| C 172—08<br>C 199—84 (2005) | Test Method for Pier Test for Refractory Mortars  |
| C 206—03                    | Specification for Finishing Hydrated Lime   |
| C 208—08a                   | Specification for Cellulosic Fiber Insulating Board   |
| C 212—00 (2006)             | Specification for Structural Clay Facing Tile   |
| C 216—07a                   | Specification for Facing Brick (Solid Masonry Units Made from Clay or Shale)  |
| C 270—08a                   | Specification for Mortar for Unit Masonry   |
| C 315—07                    | Specification for Clay Flue Liners and Chimney Pots   |
| C 317/C 317M—00 (2005)      | Specification for Gypsum Concrete   |
| C 330—05                    | Specification for Lightweight Aggregates for Structural Concrete  |
| C 331—05                    | Specification for Lightweight Aggregates for Concrete Masonry Units   |
| C 406—06e01                 | Specification for Roofing Slate   |
|                             | Specification for Standard Test Methods for Physical Testing of Gypsum, Gypsum Plasters and   |
| C 472—99 (2004)             | Gypsum Concrete   |
| C 473—07                    | Test Method for Physical Testing of Gypsum Panel Products   |
| C 474—05                    | Test Methods for Joint Treatment Materials for Gypsum Board Construction  |
| C 475/C 475M—02 (2007)      | Specification for Joint Compound and Joint Tape for Finishing Gypsum Wallboard  |
| C 503—08a                   | Specification for Marble Dimension Stone (Exterior)   |
| C 514—04                    | Specification for Nails for the Application of Gypsum Board   |
| C 516—08a                   | Specifications for Vermiculite Loose Fill Thermal Insulation  |
| C 547—07e1                  | Specification for Mineral Fiber Pipe Insulation   |
| C 549—06                    | Specification for Perlite Loose Fill Insulation   |
| C 552—07                    | Standard Specification for Cellular Glass Thermal Insulation  |
| C 557—03e01                 | Specification for Adhesives for Fastening Gypsum Wallboard to Wood Framing  |
| C 568—08a                   | Specification for Limestone Dimension Stone   |
| C 578—08b                   | Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation   |
| C 587—04                    | Specification for Gypsum Veneer Plaster   |
| C 595—08a                   | Specification for Blended Hydraulic Cements   |
| C 615—03                    | Specification for Granite Dimension Stone   |
| C 616—08                    | Specification for Quartz Dimension Stone  |
| C 629—08                    | Specification for Slate Dimension Stone   |
| C 631—09                    | Specification for Bonding Compounds for Interior Gypsum Plastering  |
| C 635/C 635M—07             | Specification for the Manufacture, Performance and Testing of Metal Suspension Systems for Acoustical Tile and Lay-in Panel Ceilings  |
| C 636/C 636M—08             | Practice for Installation of Metal Ceiling Suspension Systems for Acoustical Tile and Lay-in Panels   |
| C 645—08a                   | Specification for Nonstructural Steel Framing Members   |
| C 652—09                    | Specification for Hollow Brick (Hollow Masonry Units Made from Clay or Shale)   |
| C 726—05e1                  | Standard Specification for Mineral Fiber Roof Insulation Board  |
| C 728—05                    | Standard Specification for Perlite Thermal Insulation Board   |
| C 744—08                    | Specification for Prefaced Concrete and Calcium Silicate Masonry Units  |
| C 754—08                    | Specification for Installation of Steel Framing Members to Receive Screw-attached Gypsum Panel Products   |
| C 836—06                    | Specification for High-solids Content, Cold Liquid-applied Elastomeric Waterproofing Membrane for Use with Separate Wearing Course  |
| C 840—08                    | Specification for Application and Finishing of Gypsum Board   |
| C 841—03 (2008) e1          | Specification for Installation of Interior Lathing and Furring  |
|                             | 1 |

| ASTM Number         | Description   |
|---------------------|---|
| C 842—05            | Specification for Application of Interior Gypsum Plaster  |
| C 843—99 (2006)     | Specification for Application of Gypsum Veneer Plaster  |
| C 844—04            | Specification for Application of Gypsum Base to Receive Gypsum Veneer Plaster                   |
| C 847—09            | Specification for Metal Lath  |
| C 887—05            | Specification for Packaged, Dry Combined Materials for Surface Bonding Mortar                   |
| C 897—05            | Specification for Aggregate for Job-mixed Portland Cement-based Plaster                         |
| C 920—08            | Standard for Specification for Elastomeric Joint Sealants                                       |
| C 926—06            | Specification for Application of Portland Cement-based Plaster                                  |
| C 932—06            | Specification for Surface-applied Bonding Compounds Agents for Exterior Plastering              |
| C 933—07b           | Specification for Welded Wire Lath  |
| C 946—91 (2001)     | Specification for Practice for Construction of Dry-stacked, Surface-bonded Walls                |
| , ,                 | Specification for Steel Drill Screws for the Application of Gypsum Panel Products or Metal      |
| C 954—07            | Plaster Bases to Steel Studs from 0.033 inch (0.84 mm) to 0.112 inch (2.84 mm) in Thickness     |
|                     | Standard Specification for Load-bearing Transverse and Axial Steel Studs, Runners Tracks, and   |
| C 955—09            | Bracing or Bridging, for Screw Application of Gypsum Panel Products and Metal Plaster Bases     |
| C 956—04            | Specification for Installation of Cast-in-place Reinforced Gypsum Concrete                      |
|                     | Specification for High-solids Content, Cold Liquid-applied Elastomeric Waterproofing            |
| C 957—06            | Membrane with Integral Wearing Surface  |
|                     | Specification for Steel Self-piercing Tapping Screws for the Application of Gypsum Panel        |
| C 1002—07           | Products or Metal Plaster Bases to Wood Studs or Steel Studs                                    |
| G 1005 00           | Specification for Installation of Load Bearing (Transverse and Axial) Steel Studs and Related   |
| C 1007—08a          | Accessories   |
| C 1019—09           | Test Method of Sampling and Testing Grout   |
| C 1029—08           | Specification for Spray-applied Rigid Cellular Polyurethane Thermal Insulation                  |
| C 1032—06           | Specification for Woven Wire Plaster Base   |
| C 1047—09           | Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base                       |
|                     | Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland |
| C 1063—08           | Cement-based Plaster  |
| C 1088—09           | Specification for Thin Veneer Brick Units Made from Clay or Shale                               |
| C 1167—03           | Specification for Clay Roof Tiles   |
| C 1177/C 1177M—08   | Specification for Glass Mat Gypsum Substrate for Use as Sheathing                               |
| C 1178/C 1178M—06   | Specification for Coated Mat Water-resistant Gypsum Backing Panel                               |
| C 1186—08           | Specification for Flat Fiber Cement Sheets  |
| C 1261—07           | Specification for Firebox Brick for Residential Fireplaces                                      |
| C 1278/C 1278M—07a  | Specification for Fiber-reinforced Gypsum Panels  |
| C 1280—09           | Specification for Application of Gypsum Sheathing   |
| C 1283—07a          | Practice for Installing Clay Flue Lining  |
| C 1288—99 (2004) e1 | Standard Specification for Discrete Nonasbestos Fiber-cement Interior Substrate Sheets          |
| C 1289—08           | Standard Specification for Faced Rigid Cellular Polyisocyanurate Thermal Insulation Board       |
| C 1314—07           | Test Method for Compressive Strength of Masonry Prisms  |
| C 1325—08b          | Standard Specification for Nonasbestos Fiber-mat Reinforced Cementitious Backer Units           |
| C 1328—05           | Specification for Plastic (Stucco Cement)   |
| C 1364—07           | Standard Specification for Architectural Cast Stone   |
| C 1386—07           | Specification for Precast Autoclaved Aerated Concrete (AAC) Wall Construction Units             |
| C 1396M/C 1396M—06a | Specification for Gypsum Board  |
| C 1405—08           | Standard Specification for Glazed Brick (Single Fired, Solid Brick Units)                       |
| C 1492—03           | Standard Specification for Concrete Roof Tile   |
| C 1629/C 1629M—06   | Standard Classification for Abuse-resistant Nondecorated Interior Gypsum Panel Products and     |
|                     | Fiber-reinforced Cement Panels  |
| C 1658/C 1658M—06   | Standard Specification for Glass Mat Gypsum Panels  |
| D 25—99 (2005)      | Specification for Round Timber Piles  |
| D 41—05             | Specification for Asphalt Primer Used in Roofing, Dampproofing and Waterproofing                |
| D 43—00 (2006)      | Specification for Coal Tar Primer Used in Roofing, Dampproofing and Waterproofing               |
| D 56—05             | Test Method for Flash Point By Tag Closed Tester  |
|                     | 1   |

| A CITIM NII          | D  |
|----------------------|--|
| ASTM Number          | Description  The Market of Participant Product Advantage of Participant Product P |
| D 86—09              | Test Method for Distillation of Petroleum Products at Atmospheric Pressure   |
| D 93—08              | Test Method for Flash Point By Pensky-Martens Closed Cup Tester  |
| D 225—07             | Specification for Asphalt Shingles (Organic Felt) Surfaced with Mineral Granules   |
| D 226—06             | Specification for Asphalt-saturated Organic Felt Used in Roofing and Waterproofing   |
| D 227—03             | Specification for Coal-tar-saturated Organic Felt Used in Roofing and Waterproofing  |
| D 312—00 (2006)      | Specification for Asphalt Used in Roofing  |
| D 422—63 (2007)      | Test Method for Particle-size Analysis of Soils  |
| D 448—08             | Standard Classification for Sizes of Aggregate for Road and Bridge Construction  |
| D 450—07             | Specification for Coal-tar Pitch Used in Roofing, Dampproofing and Waterproofing   |
| D 635—06             | Test Method for Rate of Burning and/or Extent and Time of Burning of Self-supporting Plastics in a Horizontal Position   |
| D 1143/D 1143M—07e1  | Test Method for Piles Under Static Axial Compressive Load  |
| D 1227—95 (2007)     | Specification for Emulsified Asphalt Used as a Protective Coating for Roofing  |
| , ,                  | Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort [56,000  |
| D 1557—07            | $[\text{ft-lb/ft}^3 (2,700 \text{ KN m/m}^3)]$   |
| D 1761—06            | Test Method for Mechanical Fasteners in Wood   |
| D 1863—05            | Specification for Mineral Aggregate Used on Built-up Roofs   |
| D 1929—96 (2001)e01— | Test Method for Determining Ignition Properties of Plastics  |
| Withdrawn            |  |
| D 1970—09            | Specification for Self-adhering Polymer Modified Bituminous Sheet Materials Used as Steep  |
| D 1770—07            | Roof Underlayment for Ice Dam Protection   |
| D 2178—04            | Specification for Asphalt Glass Felt Used in Roofing and Waterproofing   |
| D 2487—06e1          | Practice for Classification of Soils for Engineering Purposes (Unified Soil Classification System)   |
| D 2626—04            | Specification for Asphalt Saturated and Coated Organic Felt Base Sheet Used in Roofing   |
| D 2822—05            | Specification for Asphalt Roof Cement, Asbestos Containing   |
| D 2823—05            | Specification for Asphalt Roof Coatings, Asbestos Containing   |
| D 2824—06            | Standard Specification for Aluminum-Pigmented Asphalt Roof Coating, Nonfibered, Asbestos Fibered and Fibered without Asbestos  |
| D 2843—99 (2004)e01  | Test for Density of Smoke from the Burning or Decomposition of Plastics  |
| D 2859—06            | Standard Test Method for Ignition Characteristics of Finished  |
| D 2898—08eo1         | Test Methods for Accelerated Weathering of Fireretardant-  |
| D 3019—08            | Specification for Lap Cement Used with Asphalt Roll Roofing,   |
| D 3161—09            |  |
| D 3161—09            | Test Method for a Wind Resistance of Asphalt Shingles  |
| D 3200—74 (2005)     | Standard Specification and Test Method for Establishing Recommended Design Stresses for  |
|                      | Round Timber Construction Poles  |
| D 3201—08a           | Test Method for Hygroscopic Properties of Fire-retardant-treated   |
| D 3278—96 (2004)el   | Test Methods for Flash Point of Liquids by Small Scale Closed-cup Apparatus  |
| D 3462—09            | Specification for Asphalt Shingles Made from Glass Felt and Surfaced with Mineral Granules   |
| D 3468—99 (2006)e01  | Specification for Liquid-applied Neoprene and Chlorosulfonated Polyethylene Used in Roofing  |
| D 3679—09            | and Waterproofing Specification for Rigid Poly [Vinyl Chloride (PVC) Siding]   |
| D 3689—07            |  |
|                      | Test Methods for Deep Foundations Under Static Axial Tensile Load  Prosting for Establishing Allowable Proposition for Structural Cloud Lorentzed Timber (Cluber)  |
| D 3737—08            | Practice for Establishing Allowable Properties for Structural Glued Laminated Timber (Glulam)  |
| D 3746—85 (2008)     | Test Method for Impact Resistance of Bituminous Roofing Systems  |
| D 3747—79 (2007)     | Specification for Emulsified Asphalt Adhesive for Adhering Roof Insulation   |
| D 3909—97b (2004)    | Specification for Asphalt Roll Roofing (Glass Felt) Surfaced with Mineral Granules   |
| D 3957—06            | Standard Practices for Establishing Stress Grades for Structural Members Used in Log Buildings   |
| D 4022—07            | Specification for Coal Tar Roof Cement, Asbestos Containing  |
| D 4272—08a           | Test Method for Total Energy Impact of Plastic Films by Dart Drop  |
| D 4318—05            | Test Methods for Liquid Limit, Plastic Limit and Plasticity Index of Soils   |
| D 4434/D4434M—09     | Specification for Poly (Vinyl Chloride) Sheet Roofing  |
| D 4479—07            | Specification for Asphalt Roof Coatings-Asbestos-free  |
| D 4586—07            | Specification for Asphalt Roof Cement-Asbestos-free  |
|                      |  |

| A C/TM Name have       | Description   |
|------------------------|---|
| ASTM Number D 4601—04  | Description  Specification for Aerholt costed Class Fiber Page Short Used in Pageing  |
| D 4607—04<br>D 4637—08 | Specification for Asphalt-coated Glass Fiber Base Sheet Used in Roofing Specification for EPDM Sheet Used in Single-ply Roof Membrane |
| D 4829—08a             | Test Method for Expansion Index of Soils  |
| D 4829—08a             | *   |
| D 4869—05e01           | Specification for Asphalt-saturated (Organic Felt) — Underlayment Used in Steep Slope Roofing   |
| D 4897—01              | Specification for Asphalt-coated Glass Fiber Venting Base Sheet Used in Roofing   |
| D 4945—08              | Test Method for High-strain Dynamic Testing of Piles  |
| D 4990—97a (2005)e01   | Specification for Coal Tar Glass Felt Used in Roofing and Waterproofing   |
| D 5019—07a             | Specification for Reinforced Nonvulcanized Polymeric Sheet Used in Roofing Membrane   |
| D 3019—07a             | Specification for Establishing and Monitoring Structural Capacities of Prefabricated Wood I-  |
| D 5055—09              | ioists  |
| D 5456—09              | Specification for Evaluation of Structural Composite Lumber Products  |
| D 3430—09              | Test Method of Evaluating the Flexural Properties of Fire-retardant-treated Softwood Plywood  |
| D 5516—03              | Exposed to the Elevated Temperatures  |
| D 5643—06              | Specification for Coal Tar Roof Cement, Asbestos-free   |
| D 3043—00              | Test Methods for Evaluating the Effects of Fire-retardant Treatment and Elevated Temperatures   |
| D 5664—08              | on Strength Properties of Fire-retardant-treated Lumber   |
| D 5665—99a (2006)      | Specification for Thermoplastic Fabrics Used in Cold-applied  |
| D 5726—98 (2005)       | Specification for Thermoplastic Fabrics Used in Hot-applied Roofing and Waterproofing   |
| D 6083—05e01           | Specification for Liquid Applied Acrylic Coating Used in Roofing  |
|                        | Specification for Styrene-butadiene-styrene (SBS) Modified Bituminous Sheet Materials Using   |
| D 6162—00A (2008)      | a Combination of Polyester and Glass Fiber Reinforcements   |
|                        | Specification for Styrene-butadiene-styrene (SBS) Modified Bituminous Sheet Materials Using   |
| D 6163—00 (2008)       | Glass Fiber Reinforcements  |
|                        | Specification for Styrene-butadiene-styrene (SBS) Modified Bituminous Sheet Metal Materials   |
| D 6164—05e1            | Using Polyester Reinforcements  |
|                        | Specification for Atactic Polypropylene (APP) Modified Bituminous Sheet Materials Using   |
| D 6222—08              | Polyester Reinforcements  |
| D (222 02              | Specification for Atactic Polypropylene (APP) Modified Bituminous Sheet Materials Using a   |
| D 6223—02              | Combination of Polyester and Glass Fiber Reinforcements   |
| D (200 05 1            | Specification for Fiberglass Reinforced Styrene-butadiene-styrene (SBS) Modified Bituminous   |
| D 6298—05e1            | Sheets with a Factory Applied Metal Surface   |
| D (205 00              | Practice for Calculating Bending Strength Design Adjustment Factors for Fire-retardant-treated  |
| D 6305—08              | Plywood Roof Sheathing  |
| D 6380—03 (2009)       | Standard Specification for Asphalt Roll Roofing (Organic) Felt  |
| D (500/D(500M 00       | Standard Specification for Atactic Polypropylene (APP) Modified Bituminous base Sheet   |
| D 6509/D6509M—09       | Materials Using Glass Fiber Reinforcements  |
| D 6604 09              | Standard Specification for Liquid-applied Silicone Coating Used in Spray Polyurethane Foam  |
| D 6694—08              | Roofing   |
| D 6754—02              | Standard Specification for Ketone Ethylene Ester Based Sheet Roofing  |
| D 6757—07              | Standard Specification for Inorganic Underlayment for Use with Steep Slope Roofing Products   |
| D 6841—08              | Standard Practice for Calculating Design Value Treatment Adjustment Factors for Fire-   |
| D 0841—08              | retardant-treated Lumber  |
| D 6878—08e1            | Standard Specification for Thermoplastic Polyolefin Based Sheet Roofing   |
| D 6947—07              | Standard Specification for Liquuid Applied Moisture Cured Polyurethane Coating Used in  |
| D 0947—07              | Spray Polyurethane Foam Roofing System  |
| D 7158—08d             | Standard Test Method for Wind Resistance of Sealed Asphalt Shingles (Uplift Force/Uplift  |
| D /130—00u             | Resistance Method)  |
| D 7254—07              | Standard Specification for polypropylene (PP) siding  |
| E 84—09                | Test Methods for Surface Burning Characteristics of Building Materials  |
| E 90—04                | Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building  |
|                        | Partitions and Elements   |
| E 96/E 96M—05          | Test Method for Water Vapor Transmission of Materials   |
| E 108—07a              | Test Methods for Fire Tests of Roof Coverings   |
| E 119—08a              | Test Methods for Fire Tests of Building Construction and Materials  |

| ASTM Number      | Description   |
|------------------|---|
| E 136—09         | Test Method for Behavior of Materials in a Vertical Tube Furnace at 750°C   |
|                  | Test Method for Structural Performance of Exterior Windows, Curtain Walls and Doors by  |
| E 330—02         | Uniform Static Air Pressure Difference  |
| E 331—00 (2009)  | Test Method for Water Penetration of Exterior Windows, Skylights, Doors and Curtain Walls by  |
|                  | Uniform Static Air Pressure Difference  |
|                  | Test Method for Laboratory Measurement of Impact Sound Transmission Through Floor-ceiling   |
| E 492—09         | Assemblies Using the Tapping Machine  |
|                  | Test Method for Thickness and Density of Sprayed Fire-resistive Material (SFRM) Applied to  |
| E 605—93 (2006)  | Structural Members  |
| E 681—04         |   |
| E 081—04         | Test Methods for Concentration Limits of Flammability of Chemical Vapors and Gases  |
| E 736—00 (2006)  | Test Method for Cohesion/Adhesion of Sprayed Fire-resistive Materials Applied to Structural   |
| E 014 001        | Members  The Mark of the Company of |
| E 814—08b        | Test Method of Fire Tests of Through-penetration Firestops  |
| E 970—08a        | Test Method for Critical Radiant Flux of Exposed Attic Floor Insulation Using a Radiant Heat  |
|                  | Energy Source   |
| E 1300—07e01     | Practice for Determining Load Resistance of Glass in Buildings  |
| E 1354—09        | Standard Test Method for Heat and Visible Smoke Release Rates for Materials and Products  |
| 2133. 07         | Using an Oxygen Consumption Calorimeter   |
| E 1592—05        | Test Method for Structural Performance of Sheet Metal Roof and Siding Systems by Uniform  |
|                  | Static Air Pressure Difference  |
| E 1602—03        | Guide for Construction of Solid Fuel-burning Masonry Heaters  |
| E 1886—05        | Test Method for Performance of Exterior Windows, Curtain Walls, Doors and Storm Shutters  |
| E 1880—03        | Impacted by Missiles and Exposed to Cyclic Pressure Differentials   |
| E 1966—07        | Test Method for Fire-resistant Joint Systems  |
| F 1006 00        | Specification for Performance of Exterior Windows, Glazed Curtain Walls, Doors and Impact   |
| E 1996—09        | Protective Systems Impacted by Windborne Debris in Hurricanes   |
| E 2072—04        | Standard Specification for Photoluminescent (Phosphorescent) Safety Markings  |
| E 2174—09        | Standard Practice for On-Site Inspection of Installed Fire Stops  |
|                  | Standard Test Method for Determining the Drainage Efficiency of Exterior Insulation and Finish  |
| E 2273—03        | Systems (EIFS) Clad Wall Assemblies   |
|                  | Standard Test Method for Determining Fire Resistance of Perimeter Fire Barrier Systems Using  |
| E 2307—04e01     | Intermediate-scale, Multistory Test Apparatus   |
|                  | Standard Practice for On-Site Inspection of Installed Fire Resistive Joint Systems and Perimeter  |
| E 2393—09        | Fire Barrier  |
|                  | Standard Practice for Specimen Preparation and Mounting of Textile, Paper or Vinyl Wall or  |
| E 2404—08        | Ceiling Coverings to Assess Surface Burning Characteristics   |
| E 2568—09e1      | Standard Specification for PB Exterior Insulation and Finish Systems (EIFS)   |
| E 2308—09e1      | Standard Test Method for Evaluating Water-resistive Barrier (WRB) Coatings Used Under   |
| E 2570—07        | Exterior Insulation and Finish Systems (EIFS) for EIFS with Drainage  |
|                  | Standard Practice for Specimen Preparation and Mounting of Site-fabricated Stretch Systems to   |
| E 2573—07a       |   |
|                  | Assess Surface Burning Characteristics  |
| E 2500 00        | Standard Practice for Specimen Preparation and Mounting of Reflective Insulation Materials  |
| E 2599—09        | and Radiant Barrier Materials for Building Applications to Assess Surface Burning   |
| F 2624 00        | Characteristics   |
| E 2634—08        | Standard Specification for Flat Wall Insulating Concrete Form (ICF) Systems   |
| F 547—06         | Terminology of Nails for Use with Wood and Wood-based Materials   |
| F 1346—91 (2003) | Performance Specification for Safety Covers and Labeling Requirements for All Covers for  |
|                  | Swimming Pools, Spas and Hot Tubs   |
| F 1667—05        | Specification for Driven Fasteners: Nails, Spikes and Staples   |
| F 2006—10        | Standard/Safety Specification for Window Fall Prevention Devices for Nonemergency Escape  |
|                  | (Egress) and Rescue (Ingress) Windows   |
| F 2090—08        | Specification for Window Fall Prevention Devices with Emergency Escape (Egress) Release   |
|                  | Mechanisms  |
| F 2200—05        | Standard Specification for Automated Vehicular Gate Construction  |
| G 152—06         | Practice for Operating Open Flame Carbon Arc Light Apparatus for Exposure of Nonmetallic  |
|                  |   |

| ASTM Number | Description   |
|-------------|---|
|             | Materials   |
| G 154—06    | Practice for Operating Fluorescent Light Apparatus for UV Exposure of Nonmetallic Materials |
| G 155—05a   | Practice for Operating Xenon Arc Light Apparatus for Exposure of Nonmetallic Materials      |